

Clean Cut

MORSØ



Quality, Service, and Experience
since 1911

Mitring Machine H



A semi-automatic, pneumatic mitring machine

MORSØ-H works in the same principle as the MORSØ-F, but pneumatic. MORSØ-H is activated through a safe two-hand release system, in order to protect the operator from touching the knives during work.

The MORSØ-H saves you from using your leg all the time, as the air cylinder that pulls the knives through the work piece secures an easy and effortless working procedure. The lever system is identical with the lever system on MORSØ-F. MORSØ-H can with advantage be used for repetition work, and the noise level is only 70db.

As with all other MORSØ mitring machines, there is no problem with dust, as all the waste will be lead to the ground via the waste chute.

MORSØ-H leaves the cut surface of the wood perfectly smooth and accurate, requiring no further preparation before joining.

The special lever system of the machine ensures a very easy operation. The sliding longitudinal stop and measuring scale ensure accurate repeat work.

The MORSØ-H is delivered with:
Safety guard, two-hand release system, waste chute, sliding longitudinal stop, measuring scale up to 1500 mm, adjustable fences (45-90°) and adjustable rebate supports.

Technical Data for Morsø H

Double Mitre	45°
Single Mitres, up to	90°
Cutting Width max.	100 mm
Cutting Height max.	145 mm
Square Cutting max.	65/65 mm
Measuring Scale up to	1,500 mm
Air Pressure	6 – 8 Bar
Air Consumption per stroke	15 Litres
Hose Connector	10 mm
Net Weight	90 kilos

Distributor:



dan-list A/s
MASKINFABRIK
Haraldsvej 21 - DK-8960 Randers - Denmark
Tel.: +45 8643 5155 - Fax: +45 8643 5100
e-mail: danlist@danlist.dk
www.danlist.dk - www.danlistvideos.com